

1000 liter tank in 304 stainless steel



181 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: tank has never been used; welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15

Total discharge: yes

Fixation points: 3 non adjustable feet

Legs: Set of baseplates and adjusting pieces included

Spray ball: RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11850 male

Total outlet valve: no

Adjustable legs: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.425

Power: 2,20

Voltage: three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 280 mm

Outer diameter tank: 1.450 mm

Cylinder height: 630 mm

Total height of tank: 2.100 mm

Total outer width: 1.600 mm

Total outer length: 1.900 mm

Empty weight tank: 350

SKU: 378131

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Max. Service Temperature: 80 °C

Maximum Product Density: 1200

Mobile Tank: No, it is not.

Övrig information: tank has never been used: welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 15

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: Yes

Nameplate: No, it is not.

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: Yes

Outlet Type: DIN11850 male

Outlet Valve: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)



Tank Dimensions

Cylinder Height: 630 mm

Outlet Height to Ground: 280 mm

Total Height: 2.100 mm

Outer diameter: 1.450 mm

Stirrer

Power (kW): 2,20

Motor Position: at the top

Agitator Type: propeller agitator

Speed (RPM): 1.425

Voltage: three-phase

Tjocklek på tank

Bottom: 3 mm

Cylinder: 3 mm

Top: 3 mm

Mer

Isolated: No

Weight: 350