

1000 liter tank in 304 stainless steel



46 000 SEK /st exkl moms

item available on order

Article type: brand new palletized transporttank (not ADR) - type IBC-AZ/F1

Additional information: This is a palletized container: design pressure -0.15/+2 bar; operational pressure +0.49 bar. We can take more containers in production for you.

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.600

Pressure in tank: pressure

Max. pressure (Bar): 0,49 Bar

Min. pressure (Bar): 0,15 Bar



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: yes

Top type: dished

Shape of tank: cylindrical

Bottom type: conical 30 °

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 304

Gasket manway(s): parra rubber

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11850

Total outlet valve: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 210 mm

Outer diameter tank: 1.000 mm



Cylinder height: 1.000 mm

Height of top: 230 mm

Height of bottom: 342 mm

Feet height: 456 mm

Total height of tank: 1.857 mm

Empty weight tank: 115

SKU: 374984

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank: pressure

Configuration: single-skin

Maximum Product Density: 1600

Mobile Tank: Yes

Övrig information: This is a palletized container: design pressure -0.15/+2 bar; operational pressure +0.49 bar. We can take more containers in production for you.

Agitator: No

Overpressure: 0,49 bar

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 30 °

Vacuum Pressure: 0,15 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1000

Equipment

Agitator flange: No

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: Yes

Outlet Type: DIN11850

Outlet Valve: Yes

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304



Tank Dimensions

Cylinder Height: 1.000 mm

Height on legs: 456 mm

Outlet Height to Ground: 210 mm

Total Height: 1.857 mm

Outer diameter: 1.000 mm

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 2,50 mm

Mer

Isolated: No

Weight: 115