

1000 liter tank in 304 stainless steel



97 000 SEK /st exkl moms

item available on order

Article type: brand new transport tank

Additional information: UN31A/Y transportation hazardous liquids, packing groups II and III, RID ADR

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.500

Ra inner weld: 1,60

Pressure in tank: pressure

Max. pressure (Bar): 0,10 Bar

Min. pressure (Bar): 0,10 Bar

Max. temperature (°C): 50 °C



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: flat

Shape of tank: square

Bottom type: flat sloping

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 304

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: RID ADR UN31A/Y

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 50 mm

Outlet type: BSP CAMLOCK 2"

Total outlet valve: yes

Agitator: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 150 mm

Cylinder height: 625 mm

Total height of tank: 1.160 mm

Total outer width: 1.150 mm
Total outer length: 1.150 mm
Empty weight tank: 180

SKU: 379802

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank: pressure

Configuration: single-skin

Max. Service Temperature: 50 °C

Maximum Product Density: 1500

Mobile Tank: No, it is not.

Övrig information: UN31A/Y transportation hazardous liquids, packing groups II and III, RID ADR

Agitator: No

Overpressure: 0,10 bar

Ra Internal Weld: 1,60

Tank Shape: square

Complete Drainage: Yes

Bottom Type: flat slope

Vacuum Pressure: 0,10 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1000

Equipment

Agitator flange: No

Nameplate: Yes

Food-grade: Yes

Inspected by: RID ADR UN31A/Y

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: Yes

Outlet Type: BSP CAMLOCK 2"

Outlet Valve: Yes



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 625 mm

Outlet Height to Ground: 150 mm

Total Height: 1.160 mm

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 2 mm

Mer

Isolated: No

Weight: 180