

1000 liter tank in 304 stainless steel



43 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: Duotank 2016; Previous product was beer

Volumetric volume (L): 1.000 L

Pressure in tank: pressure

Design pressure (Bar): 4,30 Bar

Max. pressure (Bar): 3 Bar

Max. temperature (°C): 30 °C

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): plastic

Gasket manway(s): EPDM

Valve: RVS 304L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 190 mm x H 220 mm

Tank outlet: inside Ø 25 mm

Outlet type: DIN11851

Total outlet valve: yes

Distance from outlet to ground: 150 mm

Outer diameter tank: 800 mm

Cylinder height: 1.920 mm

Total outer length: 2.350 mm

Empty weight tank: 250

SKU: 484901



Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Horizontal
New / Used: Used
Operating Pressure in Tank: pressure
Tank design pressure: 4.30 bar
Configuration: single-skin
Max. Service Temperature: 30 °C
Mobile Tank: No, it is not.
Övrig information: Duotank 2016; Previous product was beer
Agitator: No
Overpressure: 3 bars
Tank Shape: cylindrical
Complete Drainage:
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 25 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851
Outlet Valve: Yes



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 1,920 mm

Outlet Height to Ground: 150 mm

Outer diameter: 800 mm

Mer

Isolated: No

Weight: 250