

1000 liter tank in 304 stainless steel



50 000 SEK /st exkl moms

item available on order

Article type: brand new transport tank

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.500

Ra inner weld: 0,80

Pressure in tank: pressure

Design pressure (Bar): 3,40 Bar

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): -0,15 Bar



Max. temperature (°C): 130 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 304

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: CE0408

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Outlet type: DIN11851 male

Total outlet valve: yes

Agitator: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 202 mm

Outer diameter tank: 1.002 mm

Cylinder height: 965 mm

Total height of tank: 1.850 mm

Empty weight tank: 200

SKU: 462228

Mer information



Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: pressure
Tank design pressure: 3,40 bar
Configuration: single-skin
Max. Service Temperature: 130 °C
Maximum Product Density: 1500
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Agitator: No
Overpressure: 2 bars
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: strong conical
Vacuum Pressure: -0,15 Bar
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 1000

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: CE0408
Technical Drawing Available: Yes
Outlet Type: DIN11851 male
Outlet Valve: Yes



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 965 mm

Outlet Height to Ground: 202 mm

Total Height: 1.850 mm

Outer diameter: 1.002 mm

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 2 mm

Mer

Isolated: No

Weight: 200