

1000 liter tank in 304 stainless steel



193 000 SEK /st exkl moms

Additional information: Pharmacy; Original drawing available; vessel was subsequently slightly converted (test report from TÜV Nord is available)

Volumetric volume (L): 1.000 L

Pressure in tank: pressure

Max. pressure (Bar): 4 Bar



Max. temperature (°C): 140 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 93 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 143 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 90

Agitator: yes

Power: 5,50

Top: 8 mm

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.210 mm

Cylinder height: 1.200 mm

Total height of tank: 2.950 mm

SKU: 434117



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: insulated with heat-exchanger

Max. Service Temperature: 140 °C

Mobile Tank: No, it is not.

Övrig information: Pharmacy; Original drawing available; vessel was subsequently slightly converted (test report from TÜV Nord is available); we can't give any guarantees about the heating/cooling jacket; we can't

Additional Information2: give any guarantees about the agitator

Agitator: Yes

Overpressure: 4 bars

Complete Drainage: Yes

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 1.200 mm
Internal diameter: 1.000 mm
Total Height: 2,950 mm
Outer diameter: 1.210 mm

Stirrer

Power (kW): 5,50

Tjocklek på tank

Bottom: 6 mm
Cylinder: 6 mm
Top: 8 mm

Mer

Isolated: Yes