

1000 liter tank in 904 L



302 000 SEK /st exkl moms

Additional information: Apparatus was manufactured for a global pharmaceutical company but never put into operation there; hand hole with sight glass diameter: 285mm; incl. Südmo single seat valve SVP (outlet)

Volumetric volume (L): 1.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 60 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Top: 4,50 mm

Cylinder: 6 mm

Bottom: 4 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.194 mm

Cylinder height: 1.332 mm

Empty weight tank: 800

SKU: 458252



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature:

Mobile Tank: No, it is not.

Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 285mm; incl. Südmo single-seat valve SVP (outlet); we can't give any

Additional Information2: guarantees about the heating/cooling jacket

Agitator: No

Overpressure: 6 bars

Complete Drainage:

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1,332 mm
Internal diameter: 1.000 mm
Outer diameter: 1.194 mm

Tjocklek på tank

Bottom: 4 mm
Cylinder: 6 mm
Top: 4,50 mm

Mer

Isolated: Yes
Weight: 800