1000 liter tank in Acid-proof 316

64 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 420 mm; insulation around the cylinder (small dents in the insulating jacket)
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Position of manway: headside
Outlet of tank: 65
Agitator: yes
Number of revolutions: 56
Power: 0,75

Internal diameter tank: 990 mm
Outer diameter tank: 1.120 mm
Cylinder height: 1.430 mm
Total height of tank: 3.100 mm

SKU: 456536

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Max. Service Temperature: 90 °C
Mobile Tank: No, it is not.
Övrig information: Dairy; Diameter manhole approx. 420 mm; Insulation around the cylinder (small dents in the insulation jacket); we can't give any guarantees about the agitator
Agitator: Yes
Complete Drainage: Yes
Heating / Cooling: No
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.430 mm
Internal diameter: 990 mm
Total Height: 3.100 mm
Outer diameter: 1.120 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 56

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer
Isolated: Yes