

1000 liter tank in Acid-proof 316



215 000 SEK /st exkl moms

Additional information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating the heating medium in the double jacket; Attention: The vessel is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; switch cabinet for the electric heaters available (temperature of the double jacket can be regulated via switch cabinet); 2 ball valves for the heating jacket are included in the scope of delivery; contrary to the information in the drawing, the inside of



the vessel is not polished

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0 - 1400

Power: 0,75

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 1.150 mm

Outer diameter tank: 1.250 mm

Cylinder height: 1.000 mm

Total height of tank: 1.900 mm

Empty weight tank: 700

SKU: 453158



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Max. Service Temperature: 90 °C

Mobile Tank: No, it is not.

Övrig information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; Attention: The tank is delivered without heating medium (glycerine)

Agitator: Yes

Complete Drainage:

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.000 mm
Internal diameter: 1.150 mm
Total Height: 1.900 mm
Outer diameter: 1.250 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 0 – 1400

Tjocklek på tank

Bottom: 2 mm
Cylinder: 2 mm

Mer

Isolated: Yes
Weight: 700