

1000 liter tank in Acid-proof 316



57 000 SEK /st exkl moms

Additional information: chemistry; vessel flange made of mild steel; handholecover cladded

Volumetric volume (L): 1.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,50 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 80 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 149 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 85

Agitator: yes

Number of revolutions: 48.5 / 97

Power: 4.5 / 5.5

Top: 5,10 mm

Cylinder: 3,90 mm

Bottom: 5,30 mm

Internal diameter tank: 1.200 mm

Cylinder height: 850 mm

Total height of tank: 3.750 mm

SKU: 391247



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 143 °C

Mobile Tank: No, it is not.

Övrig information: chemistry; vessel flange made of mild steel; handholecover clad; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 0,50 bar

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 1000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 850 mm

Internal diameter: 1.200 mm

Total Height: 3.750 mm

Stirrer

Power (kW): 4.5 / 5.5

Speed (RPM): 48.5 / 97

Tjocklek på tank

Bottom: 5,30 mm

Cylinder: 3.90 mm

Top: 5,10 mm

Mer

Heat Exchanger: RVS 304

Isolated: No