

10000 liter tank in Acid-proof 316



180 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 10.000 L

Pressure in tank: ATM - atmosferic



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 435 mm

Tank outlet: inside Ø 70 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 1,10

Insulation thickness: 50

Outer diameter tank: 2.200 mm

Total height of tank: 5.750 mm



Empty weight tank: 2.000

SKU: 448055

Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 10000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 70 mm

Technical Drawing Available: No, it is not.



Material Overview

Material: Acid-resistant 316

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Exterior cladding: RVS 304

Tank Dimensions

Total Height: 5.750 mm

Outer diameter: 2,200 mm

Stirrer

Power (kW): 1,10

Motor Position: at the top

Agitator Type: propeller agitator

Mer

Insulation Thickness OW: 50

Isolated: No

Weight: 2.000