

10000 liter tank in GAP/Plast



144 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

Volumetric volume (L): 10.000 L

Max. density P (kg/m³): 1.180

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: polyester (fiberglass)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: on skirt

Manway(s): polyester

Fixation point(s): polyester

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 600 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 45

Power: 1,10

Voltage: three-phase

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.120 mm

Total height of tank: 3.788 mm

Empty weight tank: 1.040

SKU: 486665



Mer information

Product Description

Material: GAP/Plast

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Max. Service Temperature: 95 °C

Maximum Product Density: 1180

Mobile Tank: No, it is not.

Övrig information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: dish

Heating / Cooling: No

Contact Surface: polyester (fiberglass)

Volume in liters: 10000

Equipment

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: Yes

Material Overview

Material: GAP/Plast

Fixing point(s): polyester



Tank Dimensions

Internal diameter: 2,000 mm

Total Height: 3.788 mm

Outer diameter: 2.120 mm

Stirrer

Power (kW): 1,10

Motor Position: at the top

Agitator Type: propeller agitator

Speed (RPM): 45

Voltage: three-phase

Mer

Isolated: No

Weight: 1.040