

10000 liters tank in Stainless 304



161 000 SEK /st exkl moms

Additional information: Dairy; 1 loose railing and 3 load cells are included in the scope of delivery; specified total height including railing, without load cells; using the load cells would increase the total height by approx. 250 mm; 1 external pipeline; small dents in the cylinder

Volumetric volume (L): 10.000 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Number of revolutions: 20 / 40

Power: 1.5 / 2.2

Internal diameter tank: 2.190 mm

Cylinder height: 3.000 mm

Total height of tank: 5.750 mm

SKU: 452882

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Dairy; 1 loose railing and 3 load cells are included in the scope of delivery; specified total height including railing, without load cells; using the load cells would increase the total height by

Additional Information2: approx. 250 mm; 1 external pipeline; small dents in the cylinder

Agitator: No

Complete Drainage: No, it is not.

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 10000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 3,000 mm

Internal diameter: 2,190 mm

Total Height: 5.750 mm

Stirrer

Power (kW): 1.5 / 2.2

Speed (RPM): 20 / 40



Mer

Isolated: No