

100000 liters tank in Stainless 304



735 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 100.000 L

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes
Mobile tank: no
Top type: conical
Shape of tank: conical
Bottom type: conical

Bottom outlet: yes
Total discharge: yes
Fixation points: on skirt
Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: cylinder
Hinged lid: yes
Outlet type: DIN11850
Outlet of tank: DN65
Agitator: yes

Agitator type: propeller agitator
Position engine: in the bottom
Number of revolutions: 725/42 - 1470/86
Power: 2.7/5.5
Voltage: 400 V - three-phase

Current: 9.20/11.00
Insulation body: yes
finish of the outer jacket: welded
Insulation thickness: 50

Internal diameter tank: 4.000 mm

Distance from outlet to ground: 900 mm

Outer diameter tank: 4.135 mm

Cylinder height: 8.000 mm

Total height of tank: 10.830 mm

Total outer width: 4.300 mm

Total outer length: 11.000 mm

Empty weight tank: 8.000

SKU: 418697

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Stainless steel finish: 2b

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Ra Internal Weld: 0,80

Tank Shape: conical

Complete Drainage: Yes

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 100000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Technical Drawing Available: No, it is not.

Outlet Type: DIN11850

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Exterior cladding: RVS 304



Tank Dimensions

Cylinder Height: 8,000 mm
Internal diameter: 4,000 mm
Outlet Height to Ground: 900 mm
Total Height: 10,830 mm
Outer diameter: 4.135 mm

Stirrer

Power (kW): 2.7/5.5
Motor Position: in the bottom
Agitator Type: propeller agitator
Speed (RPM): 725/42 – 1470/86
Voltage: 400 V – three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Jacket insulation: Yes
Insulation material: Rockwool

Mer

Insulation Thickness OW: 50
Isolated: Yes
Weight: 8.000