

100000 liters tank in Stainless 304



714 000 SEK /st exkl moms

Additional information: PH glycerin; Electrical trace heating using external heating cables (no guarantee of functionality); Manhole diameter 600 mm (manhole cover may no longer exist); some residues of previous content

Volumetric volume (L): 100.000 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 60 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 80

Top: 5 mm

Bottom: 9 mm

Internal diameter tank: 2.900 mm

Cylinder height: 15.140 mm

SKU: 402539

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Max. Service Temperature: 60 °C

Mobile Tank: No, it is not.

Övrig information: PH glycerin; Electrical trace heating using external heating cables (no guarantee of functionality); Manhole diameter 600 mm (manhole cover may no longer exist); some residues of previous content

Agitator: No

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 100000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 15.140 mm

Internal diameter: 2,900 mm

Tjocklek på tank

Bottom: 9mm

Top: 5 mm



Mer

Isolated: Yes