

102000 liters tank in Stainless 304



367 000 SEK /st exkl moms

Article type: second-hand storage tank

Volumetric volume (L): 102.000 L

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical

Shape of tank: cylindrical

Bottom type: flat sloping 3 °

Total discharge: yes

Insulation material: Rockwool

Outer jacket (ornamental wall): galvanised steel

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: yes

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 405 mm x H 505 mm

Tank outlet: inside Ø 100 mm

Outlet type: PIPE END

Total outlet valve: no, optional

Agitator: no, optional

Cylinder: 50

Insulation body: yes

finish of the outer jacket: riveted

Internal diameter tank: 3.140 mm

Outer diameter tank: 3.400 mm

Cylinder height: 13.250 mm

Total height of tank: 14.350 mm

Empty weight tank: 5.000

SKU: 380255



Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Stainless steel finish: 2b
Configuration: insulated
Mobile Tank: No, it is not.
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: flat sloping 3 °
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 102000

Equipment

Product Dokument finns: No, it is not.
Agitator flange: Yes
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 100 mm
Technical Drawing Available: No, it is not.
Outlet Type: PIPE END

Material Overview

Material: Stainless steel 304
Insulation material: Rockwool
Exterior cladding: galvanized steel



Tank Dimensions

Cylinder Height: 13.250 mm
Internal diameter: 3.140 mm
Total Height: 14.350 mm
Outer diameter: 3,400 mm

Outer Cladding and Insulation Thickness

External jacket finish: riveted
Jacket insulation: Yes
Insulation material: Rockwool

Mer

Cylinder OW: 50
Isolated: Yes
Weight: 5.000