1023 liter tank in Stainless 304

90 000 SEK /st exkl moms

Additional information: frame Fe (galvanized)
Volumetric volume (L): 1.023 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 14 L
Max Overpressure: 2,50 Bar
Max. working temperature: 95 °C
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 270
Power: 1,1
Internal diameter tank: 1.080 mm

Cylinder height: 1.000 mm
Total height of tank: 2.000 mm

SKU: 479490

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 80 °C
Mobile Tank: No, it is not.
Övrig information: frame Fe (galvanized); we can't give any guarantees about the agitator
Agitator: Yes
Complete Drainage: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 1023

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.000 mm
Internal diameter: 1,080 mm
Total Height: 2,000 mm

Stirrer

Power (kW): 1,1
Speed (RPM): 270

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer

Heat Exchanger: RVS 304
Isolated: No