

10300 liter tank in Acid-proof 316



141 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Year of manufacture 2025; Tank in very good condition; Drawing on request

Volumetric volume (L): 10.300 L

Max. density P (kg/m³): 1.000

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Fixation points: 4 attachment points

Insulation material: PIR

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 432 mm x H 532 mm

Hinged lid: yes

Tank outlet: inside Ø 60 mm

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 5 mm

Top: 3

Insulation top: yes

Cylinder: 3

Insulation body: yes

finish of the outer jacket: welded

Insulation thickness: 80

Internal diameter tank: 2.100 mm

Distance from outlet to ground: 145 mm



Outer diameter tank: 2.280 mm

Cylinder height: 3.000 mm

Total height of tank: 3.300 mm

Empty weight tank: 1.850

SKU: 580472

Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Max. Service Temperature: 100 °C

Maximum Product Density: 1000

Mobile Tank: No, it is not.

Övrig information: Year of manufacture 2025; Tank in very good condition; Drawing on request

Agitator: No

Tank Shape: cylindrical

Complete Drainage: No, it is not.

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 316L (V4A)

Volume in liters: 10300



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 60 mm
Technical Drawing Available: Yes

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L
Insulation material: PIR
Exterior cladding: RVS 304L

Tank Dimensions

Cylinder Height: 3,000 mm
Internal diameter: 2.100 mm
Outlet Height to Ground: 145 mm
Total Height: 3.300 mm
Outer diameter: 2,280 mm

Tjocklek på tank

Bottom: 5 mm
Cylinder: 3 mm
Top: 3 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded
Jacket insulation: Yes
Insulation material: PIR



Mer

Cylinder OW: 3

Insulation material: Yes

Insulation Thickness OW: 80

Isolated: Yes

Weight: 1.850