1150 liter tank in stainless steel 304

118 000 SEK /st exkl moms

Volumetric volume (L): 1.150 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Fixation point(s): plastic
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: DN50 DIN 11851
Number of revolutions: 0 - 12
Power: 0,75
Internal diameter tank: 1.200 mm
Cylinder height: 938 mm

Total height of tank: 1.720 mm

SKU: 394739

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: single-skin
Max. Service Temperature: 80 °C
Mobile Tank: No, it is not.
Agitator: No
Complete Drainage: No, it is not.
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 1150

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): plastic

Tank Dimensions

Cylinder Height: 938 mm
Internal diameter: 1.200 mm
Total Height: 1.720 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 0 – 12

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer
Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor