

1150 liter tank in stainless steel 304



117 000 SEK /st exkl moms

Volumetric volume (L): 1.150 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 4 L

Max Overpressure: 5 Bar

Max. working temperature: 80 °C

Heat exchanger: RVS 304

Fixation point(s): plastic

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0-190

Power: 0,75

Internal diameter tank: 1.200 mm

Cylinder height: 938 mm

Total height of tank: 1.680 mm

SKU: 392936



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 80 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1150

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: Yes

Material Overview

Material: Stainless steel 304

Fixing point(s): plastic

Tank Dimensions

Cylinder Height: 938 mm

Internal diameter: 1.200 mm

Total Height: 1.680 mm



Stirrer

Power (kW): 0,75

Speed (RPM): 0-190

Mer

Heat Exchanger: RVS 304

Isolated: No