1169 liter tank in Acid-proof 316

258 000 SEK /st exkl moms

Volumetric volume (L): 1.169 L
Pressure in tank: pressure
Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Max Overpressure: 2,50 Bar
Max. working temperature: 140 °C
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 0 - 12
Power: 0,75

Cylinder: 4 mm
Bottom: 4 mm
Internal diameter tank: 1.192 mm
Outer diameter tank: 1.360 mm
Cylinder height: 1.000 mm

Total height of tank: 2.250 mm

SKU: 441059

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated with heat-exchanger
Max. Service Temperature: 100 °C
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Complete Drainage: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1169

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.000 mm
Internal diameter: 1.192 mm
Total Height: 2.250 mm
Outer diameter: 1.360 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Stirrer
Power (kW): 0,75
Speed (RPM): 0 – 12

Tjocklek på tank
Bottom: 4 mm
Cylinder: 4 mm

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor