

120 liter tank in stainless steel 304



33 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: we can't give any guarantees about the heating/cooling jacket

Volumetric volume (L): 120 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no



Top type: large seperat lid

Shape of tank: cylindrical

Bottom type: flat

Total discharge: yes

Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Water pressure HE: 2 Bar

Steam pressure HE: 1 Bar

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Agitator: no

Internal diameter tank: 500 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 600 mm

Cylinder height: 650 mm

Total height of tank: 1.200 mm

Empty weight tank: 250

SKU: 475060



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: isolert med varmeveksler

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: flat

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 120

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Exterior cladding: RVS 304



Tank Dimensions

Cylinder Height: 650 mm

Internal diameter: 500 mm

Outlet Height to Ground: 300 mm

Total Height: 1.200 mm

Outer diameter: 600 mm

Heat exchangers

Vapor pressure heat exchanger: 1 bar

Position värmeväxlare: the complete cylinder

Type of Heat Exchanger on Cylinder: dimple jacket

Water Pressure Heat Exchanger: 2 bars

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Heat Exchanger: RVS 304

Isolated: Yes

Weight: 250