

12000 liters tank in Stainless 304



133 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: milk tanks; we can't give any guarantees about the agitator

Volumetric volume (L): 12.000 L

Ra inner weld: 0,80

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 304

Manway(s): RVS 304

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: at the top

Height manhole 1 (mm): 420 mm

CIP spray ball: yes

Tank outlet: inside Ø 70 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: in the bottom

Number of revolutions: 100

Power: 1,50

Voltage: three-phase

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 2.150 mm

Distance from outlet to ground: 500 mm



Outer diameter tank: 2.300 mm

Cylinder height: 2.800 mm

Total height of tank: 4.700 mm

Empty weight tank: 1.100

SKU: 566081

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: milk tanks; we can't give any guarantees about the agitator

Agitator: Yes

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 12000



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 70 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 2,800 mm
Internal diameter: 2,150 mm
Outlet Height to Ground: 500 mm
Total Height: 4,700 mm
Outer diameter: 2,300 mm

Stirrer

Power (kW): 1,50
Motor Position: in the bottom
Agitator Type: propeller agitator
Speed (RPM): 100
Voltage: three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Insulation Thickness OW: 50

Isolated: Yes

Weight: 1.100