

1212 liter tank in Stainless 304



101 000 SEK /st exkl moms

Additional information: solvent; the double jacket is used as a protective jacket with leak monitoring

Volumetric volume (L): 1.212 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 4 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: no

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

SKU: 433565

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 50 °C

Mobile Tank: No, it is not.

Övrig information: solvent; the double jacket is used as a protective jacket with leak monitoring

Agitator: No

Overpressure: 4 bars

Complete Drainage: No, it is not.

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1212

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Mer

Isolated: No