1229 liter tank in Syrafast 316

221 000 SEK /st exkl moms

Additional information: Tank was rebuilt in 2011; further technical documents available
Volumetric volume (L): 1.229 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 88 L
Max Overpressure: 3 Bar

Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 30
Top: 6,50 mm

Cylinder: 8 mm
Bottom: 5,70 mm
Internal diameter tank: 1.188 mm
Outer diameter tank: 1.347 mm
Cylinder height: 750 mm

Total height of tank: 2.350 mm

SKU: 417212

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 150 °C
Mobile Tank: No, it is not.
Övrig information: Pharmacy; Tank was rebuilt in 2011; further technical documents available; we can't give any guarantees about the heating/cooling jacket
Agitator: No
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1229

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 750 mm
Internal diameter: 1.188 mm
Total Height: 2.350 mm
Outer diameter: 1.347 mm

Tjocklek på tank

Bottom: 5,70 mm
Cylinder: 8 mm
Top: 6,50 mm

Mer

Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se