

124 liter tank in Acid-proof 316



51 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe inside the tank (see pictures); GEMÜ bottom outlet diaphragm valve at the outlet. Technical documentation available from the manufacturer.

Volumetric volume (L): 124 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 14 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 50 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: clamp

Internal diameter tank: 500 mm

Cylinder height: 680 mm

Total height of tank: 1.250 mm

SKU: 481714



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 150 °C

Mobile Tank: No, it is not.

Övrig information: pharmacy; Filling pipe inside the tank (see pictures); GEMÜ bottom outlet diaphragm valve at the outlet. Technical documentation available from the manufacturer; we can't give any guarantees about

Additional Information2: the heating/cooling jacket

Agitator: No

Overpressure: 3 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 124

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 680 mm

Internal diameter: 500 mm

Total Height: 1.250 mm

Mer

Heat Exchanger: RVS 304

Isolated: Yes