

1250 liter tank in stainless steel 304



28 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator

Volumetric volume (L): 1.250 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no



Mobile tank: no

Top type: flat

Shape of tank: rectangular

Bottom type: flat

Total discharge: no

Fixation points: 4 stackable frame

Manway(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 385 mm

Agitator: yes

Position engine: at the top

Number of revolutions: 250

Power: 1,10

Voltage: three-phase

Cylinder height: 1.160 mm

Total height of tank: 2.350 mm

Total outer width: 1.015 mm

Total outer length: 1.215 mm

Empty weight tank: 300

SKU: 572414



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: rectangular

Complete Drainage: No, it is not.

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1250

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Tank Dimensions

Cylinder Height: 1.160 mm

Total Height: 2.350 mm



Stirrer

Power (kW): 1,10

Motor Position: at the top

Speed (RPM): 250

Voltage: three-phase

Mer

Isolated: No

Weight: 300