127 liter tank in Acid-proof 316

163 000 SEK /st exkl moms

Additional information: Pharmacy
Volumetric volume (L): 127 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 24 L
Max Overpressure: 2,50 Bar

Max onderdruk: 1 Bar
Max. working temperature: 143 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN25 DIN 11851
Agitator: yes

Number of revolutions: 690
Power: 0,37
Cylinder: 3 mm
Bottom: 3 mm
Internal diameter tank: 500 mm

Outer diameter tank: 600 mm
Cylinder height: 500 mm
Total height of tank: 1.650 mm

SKU: 429272

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 143 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 127

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 500 mm
Internal diameter: 500 mm
Total Height: 1.650 mm
Outer diameter: 600 mm

Stirrer

Power (kW): 0,37
Speed (RPM): 690

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm

Mer

Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor