

1270 liters tank in Stainless 304



90 000 SEK /st exkl moms

Additional information: Bottom of the inner tank with small dents

Volumetric volume (L): 1.270 L

Pressure in tank: pressure

Max. temperature (°C): 95 °C



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 3 Bar

Max. working temperature: 95 °C

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 25 / 49

Power: 0.3 / 0.6

Top: 3 mm

Cylinder: 3 mm

Bottom: 2,50 mm

Internal diameter tank: 1.200 mm

Outer diameter tank: 1.338 mm

Cylinder height: 1.000 mm

Total height of tank: 2.650 mm

SKU: 486326



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 95 °C

Mobile Tank: No, it is not.

Övrig information: Dairy; Possibly also double jacket or former double jacket around the lower bottom; lower bottom of the inner tank with smaller dents; we can't give any guarantees about the heating/cooling jacket;

Additional Information2: we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1270

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 970 mm
Internal diameter: 1.180 mm
Total Height: 2,650 mm
Outer diameter: 1,320 mm

Stirrer

Power (kW): 0.3 / 0.6
Speed (RPM): 25 / 49

Tjocklek på tank

Bottom: 2,50 mm
Cylinder: 3 mm
Top: 3 mm

Mer

Heat Exchanger: RVS 304
Isolated: Yes