

1280 liter tank in Acid-proof 316



120 000 SEK /st exkl moms

Additional information: Pressure Equipment Directive 97/23/EC Annex III Module H/H1 Material certificates
3.1 B Radiographic testing of weld seams (2%)

Volumetric volume (L): 1.280 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 3 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max. working temperature: 95 °C

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Top: 8 mm

Cylinder: 3 mm

Bottom: 4 mm

Internal diameter tank: 1.100 mm

Cylinder height: 1.000 mm

Total height of tank: 2.110 mm

Empty weight tank: 500

SKU: 392750



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: insulated with heat-exchanger

Max. Service Temperature: 130 °C

Mobile Tank: No, it is not.

Övrig information: Pressure Equipment Directive 97/23/EC Annex III Module H/H1 Material certificates 3.1 B Radiation test of welds (2%); we can't give any guarantees about the heating/cooling jacket

Agitator: No

Overpressure: 3 bars

Complete Drainage: Yes

Vacuum Pressure: 3 bars

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 1280

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.000 mm

Internal diameter: 1.100 mm

Total Height: 2.110 mm



Tjocklek på tank

Bottom: 4 mm

Cylinder: 3 mm

Top: 8 mm

Mer

Heat Exchanger: RVS 304

Isolated: Yes

Weight: 500