

1300 liter tank in Stainless 304



88 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type CCT-ES-HL

Volumetric volume (L): 1.300 L

Finish stainless steel: pickled

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): -0,15 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: yes

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical 45 °

Total discharge: yes

Fixation points: 4 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Working temperature HE cylinder: 80 °C

Type of HE on the bottom: dimple-jacket

Heat exchanger: RVS 304

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 304L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional



Technical drawing included: yes
Registration plate on the tank: yes
Inspection of: TUV
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 400 mm
CIP spray ball: no, optional
Tank outlet: inside Ø 32 mm
Outlet type: DIN11851 male

Total outlet valve: yes
Agitator: no, optional
Top: 2 mm
Cylinder: 2 mm
Bottom: 2,50 mm

Distance from outlet to ground: 200 mm
Outer diameter tank: 1.140 mm
Cylinder height: 965 mm
Height of bottom: 496 mm
Feet height: 695 mm

Total height of tank: 2.020 mm
Empty weight tank: 155

SKU: 378209

Mer information



Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: pressure
Stainless steel finish: pickled
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 130 °C
Mobile Tank: Yes
Agitator: No
Overpressure: 2 bars
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: strong conical 45 °
Vacuum Pressure: -0,15 Bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 1300

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 32 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male
Outlet Valve: Yes

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304



Tank Dimensions

Cylinder Height: 965 mm

Height on legs: 695 mm

Outlet Height to Ground: 200 mm

Total Height: 2,020 mm

Outer diameter: 1.140 mm

Heat exchangers

Operating Temperature Heat Exchanger Cylinder: 80 °C

Position värmeväxlare: the complete cylinder

Type of Heat Exchanger on Cylinder: dimple jacket

Bottom Heat Exchanger Type: dimple jacket

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 2 mm

Mer

Heat Exchanger: RVS 304

Isolated: No

Weight: 155