1350 liter tank in Acid-proof 316

177 000 SEK /st exkl moms

Additional information: Various technical documents available; vessels were suspended by the previous operator in a ring with load cells, which was embedded in the floor (1 ring each is included in the scope of delivery; see photos)
Volumetric volume (L): 1.350 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 80 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 140 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available

Agitator: yes
Number of revolutions: 412
Power: 0,75
Top: 4,50 mm
Internal diameter tank: 1.000 mm

Outer diameter tank: 1.250 mm
Cylinder height: 1.460 mm
Total height of tank: 2.650 mm

SKU: 478383

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: isolert med varmeveksler
Max. Service Temperature: 130 °C
Mobile Tank: No, it is not.
Övrig information: Pharmacy; Various technical documents available; the previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery;
Additional Information2: see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1350

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material Overview
Material: Acid-resistant 316

Tank Dimensions
Cylinder Height: 1.460 mm
Internal diameter: 1.000 mm
Total Height: 2,650 mm
Outer diameter: 1.250 mm

Stirrer
Power (kW): 0,75
Speed (RPM): 412

Tjocklek på tank
Top: 4,50 mm

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor