1380 liters tank in Acid-proof 316

62 000 SEK /st exkl moms

Additional information: Chemistry; some residues of previous content; manhole cover plated; Metallic discolouration inside
Volumetric volume (L): 1.380 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 40 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: flange DN50
Top: 10 mm

Cylinder: 6 mm
Bottom: 8 mm
Internal diameter tank: 1.200 mm
Cylinder height: 850 mm
Total height of tank: 2.500 mm

SKU: 397727

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 200 °C
Mobile Tank: No, it is not.
Övrig information: Chemistry; some residues of previous content;manhole cover plated;Metallic discolouration inside
Agitator: No
Overpressure: 6 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1380

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Cylinder Height: 850 mm
Internal diameter: 1.200 mm
Total Height: 2.500 mm

Tjocklek på tank
Bottom: 8 mm
Cylinder: 6 mm
Top: 10 mm

Mer
Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor