1450 liter tank in Acid-proof 316

206 000 SEK /st exkl moms

Additional information: Pharmacy
Volumetric volume (L): 1.450 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 80 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 120 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 25

Agitator: yes
Number of revolutions: 690
Power: 1,10
Cylinder: 6 mm
Bottom: 7,10 mm

Internal diameter tank: 1.400 mm
Outer diameter tank: 1.456 mm
Cylinder height: 500 mm
Total height of tank: 2.050 mm

SKU: 412325

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 140 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1450

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 500 mm
Internal diameter: 1.400 mm
Total Height: 2,050 mm
Outer diameter: 1.456 mm

Stirrer

Power (kW): 1,10
Speed (RPM): 690

Tjocklek på tank

Bottom: 7,10 mm
Cylinder: 6 mm

Mer

Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor