150 liter tank in Acid-proof 316

64 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type VC-SLO
Additional information: Ra=<0.8µm
Volumetric volume (L): 150 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: large seperat lid
Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes
Fixation points: 3 non adjustable feet

Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Inspection of: TUV
Flange for agitator: no
CIP spray ball: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN11850 female

Total outlet valve: no, optional
Agitator: no
Top: 2 mm
Cylinder: 3 mm
Bottom: 3 mm

Distance from outlet to ground: 250 mm
Outer diameter tank: 605 mm
Cylinder height: 500 mm
Total height of tank: 1.000 mm
Empty weight tank: 50

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

SKU: 379337

Mer information

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 80 °C
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Övrig information: Ra=<0.8µm
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 20 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 150

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Equipment
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: Yes
Outlet Type: DIN11850 female

Material Overview
Material: Acid-resistant 316
Fixing point(s): RVS 304L

Tank Dimensions
Cylinder Height: 500 mm
Outlet Height to Ground: 250 mm
Total Height: 1.000 mm
Outer diameter: 605 mm

Tjocklek på tank
Bottom: 3 mm
Cylinder: 3 mm
Top: 2 mm

Mer
Isolated: No
Weight: 50

Rodervägen 57
891 78 Bonässund
info@processoverskott.se