

1500 liter tank in 304 stainless steel



108 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: The lid for the smaller connection on the top is missing, the cap for the electromotor is missing, the nuts for the manway are missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 1.500 L

Ra inner weld: 0,80

Pressure in tank: pressure

Design pressure (Bar): 5,25 Bar

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): -1 Bar



Max. temperature (°C): 135 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 non adjustable feet

Water pressure HE: 5 Bar

Hydraulic test pressure: 6,89 Bar

Working temperature HE cylinder: 135 °C

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Total outlet valve: yes

Agitator: yes

Agitator type: tripad

Position engine: in the bottom

Outer diameter tank: 1.500 mm

Total height of tank: 2.000 mm

Empty weight tank: 750

SKU: 381593

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Tank design pressure: 5,25 bar

Configuration: isolert med varmeveksler

Max. Service Temperature: 135 °C

Mobile Tank: No, it is not.

Övrig information: The lid for the smaller connection on the top is missing, the cap for the electromotor is missing, the nuts for the manway are missing; we can't give any guarantees about the heating/cooling jacket;

Additional Information2: we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3 bars

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: dish

Vacuum Pressure: -1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1500

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Technical Drawing Available: No, it is not.

Outlet Valve: Yes



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Tank Dimensions

Total Height: 2,000 mm

Outer diameter: 1.500 mm

Heat exchangers

Operating Temperature Heat Exchanger Cylinder: 135 °C

Bottom hydrostatic test pressure: 6.89 bar

Hydrostatic test pressure: 6.89 bar

Water Pressure Heat Exchanger: 5 bars

Stirrer

Motor Position: in the bottom

Agitator Type: tripad

Mer

Isolated: Yes

Weight: 750