

1500 liter tank in Acid-proof 316



107 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 1.500 L

Max. density P (kg/m³): 1.300

Ra inner weld: 1,60

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: flat

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Fixation point(s): RVS 304L

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Outlet of tank: 50

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 347

Power: 2,20

Voltage: three-phase

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 1.350 mm

Cylinder height: 1.000 mm

Height of top: 1.626 mm

Feet height: 626 mm

Total height of tank: 2.470 mm



Empty weight tank: 350

SKU: 572330

Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Stainless steel finish: 2b

Configuration: single-skin

Max. Service Temperature: 80 °C

Maximum Product Density: 1300

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Ra Internal Weld: 1,60

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical 15 °

Heating / Cooling: No

Contact Surface: SS AISI 316L (V4A)

Volume in liters: 1500



Equipment

Agitator flange: No
Nameplate: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 1.000 mm
Height on legs: 626 mm
Outlet Height to Ground: 300 mm
Total Height: 2,470 mm
Outer diameter: 1.350 mm

Stirrer

Power (kW): 2,20
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 347
Voltage: three-phase

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm

Mer

Isolated: No
Weight: 350