

15000 liter tank in Acid-proof 316



234 000 SEK /st exkl moms

Additional information: Food production; Manhole approx. 410 x 510 mm; heating coil around approx. 1,800 mm of the lower cylinder height; slight signs of corrosion inside the tanks; pipe end cut flush

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 90 L

Max Overpressure: 3 Bar

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 35

Agitator: yes

Number of revolutions: 910

Power: 0,55

Internal diameter tank: 2.090 mm

Outer diameter tank: 2.290 mm

Total height of tank: 6.550 mm

SKU: 411383

Mer information



Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Food production; Manhole approx. 410 x 510 mm; heating coil around approx. 1,800 mm of the lower cylinder height; slight signs of corrosion inside the tanks; pipe end cut flush; we can't give any

Additional Information2: guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 15000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Internal diameter: 2,090 mm

Total Height: 6.550 mm

Outer diameter: 2,290 mm



Stirrer

Power (kW): 0,55

Speed (RPM): 910

Mer

Isolated: Yes