

15000 liters tank in Stainless 304



202 000 SEK /st exkl moms

Additional information: Double jacket with trickle ring - only suitable for unpressurized tempering

Volumetric volume (L): 15.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar



Min. pressure (Bar): 0,80 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 145

Power: 3

Top: 10 mm

Cylinder: 8 mm

Bottom: 10 mm

Internal diameter tank: 2.300 mm

Cylinder height: 3.250 mm

Total height of tank: 5.100 mm

Empty weight tank: 3.000

SKU: 568142



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 145 °C

Mobile Tank: No, it is not.

Övrig information: Food; Double jacket with trickle ring – only suitable for unpressurized tempering; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3,50 bar

Complete Drainage: Yes

Vacuum Pressure: 0,80 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 15000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 3.250 mm
Internal diameter: 2,300 mm
Total Height: 5.100 mm

Stirrer

Power (kW): 3
Speed (RPM): 145

Tjocklek på tank

Bottom: 10 mm
Cylinder: 8 mm
Top: 10 mm

Mer

Isolated: Yes
Weight: 3.000