

15000 liters tank in Stainless 304



211 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 500 mm
Tank outlet: inside Ø 80 mm
Total outlet valve: no

Agitator: yes
Agitator type: tripad
Position engine: at the top
Number of revolutions: 18 / 36
Power: 2,20

Voltage: three-phase
Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 60

Internal diameter tank: 2.650 mm
Distance from outlet to ground: 600 mm
Outer diameter tank: 2.800 mm
Cylinder height: 2.750 mm

Total height of tank: 5.400 mm

Empty weight tank: 1.300

SKU: 381626

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: isolert med varmeveksler

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 15000



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: No, it is not.
Outlet Valve: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 2,750 mm
Internal diameter: 2,650 mm
Outlet Height to Ground: 600 mm
Total Height: 5,400 mm
Outer diameter: 2,800 mm

Stirrer

Power (kW): 2,20
Motor Position: at the top
Agitator Type: tripad
Speed (RPM): 18 / 36
Voltage: three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Insulation Thickness OW: 60

Isolated: Yes

Weight: 1.300