

15000 liters tank in Stainless 304



113 000 SEK /st exkl moms

Article type: second-hand

Additional information: Steel heating pipes 2" in the skirt below the bottom of the tank;

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Fixation points: on skirt

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304L

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 32 mm

Outlet type: DIN11851 female

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2,50 mm

Bottom: 3 mm

Insulation top: yes

Insulation body: yes

finish of the outer jacket: welded

Insulation thickness: 50

Tank capacity top cylinder: 15.000 L

Internal diameter tank: 2.400 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 2.500 mm

Cylinder height: 3.380 mm

Total height of tank: 4.250 mm

Empty weight tank: 2.000

SKU: 386429

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Steel heating pipes 2" in the skirt below the bottom of the tank;

Agitator: No

Tank Shape: cylindrical

Complete Drainage: No, it is not.

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 15000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 32 mm

Technical Drawing Available: No, it is not.

Outlet Type: DIN11851 female



Material Overview

Material: Stainless steel 304
Insulation material: Rockwool
Exterior cladding: RVS 304L

Tank Dimensions

Cylinder Height: 3,380 mm
Internal diameter: 2,400 mm
Outlet Height to Ground: 300 mm
Total Height: 4.250 mm
Outer diameter: 2.500 mm

Tjocklek på tank

Bottom: 3 mm
Cylinder: 2,50 mm
Top: 2,50 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded
Jacket insulation: Yes
Insulation material: Rockwool

Mer

Insulation material: Yes
Insulation Thickness OW: 50
Isolated: Yes
Weight: 2.000