1700 liter tank in Acid-proof 316



307 000 SEK /st exkl moms

Additional information: Fully comprehensive documentation in accordance with pharmaceutical industry standards included in the scope of delivery; device was manufactured for a global pharmaceutical company but never put into operation there; hand hole with sight glass diameter: 150 mm; incl. Südmo single seat valve SVP (outlet)
Volumetric volume (L): 1.700 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 57 L
Max Overpressure: 10 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Top: 15 mm

Cylinder: 5 mm
Bottom: 8 mm
Internal diameter tank: 1.200 mm
Outer diameter tank: 1.400 mm
Cylinder height: 1.500 mm

Total height of tank: 2.752 mm
Empty weight tank: 1.800

SKU: 441227

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 150 °C
Mobile Tank: No, it is not.
Övrig information: Full set of pharma-compliant technical documentation included in delivery; tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass
Additional Information2: diameter: 150mm; incl. Südmo single-seat valve SVP (outlet); we can't give any guarantees about the heating/cooling jacket
Agitator: No
Overpressure: 6 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1700

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material Overview
Material: Acid-resistant 316

Tank Dimensions
Cylinder Height: 1.500 mm
Internal diameter: 1.200 mm
Total Height: 2.752 mm
Outer diameter: 1.400 mm

Tjocklek på tank
Bottom: 8 mm
Cylinder: 5 mm
Top: 15mm

Mer
Isolated: Yes
Weight: 1.800

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor