

1700 liter tank in Stainless 304



70 000 SEK /st exkl moms

Additional information: Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator

Volumetric volume (L): 1.700 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 210 L

Max Overpressure: 2,50 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 72

Power: 1,50

Internal diameter tank: 1.330 mm

Outer diameter tank: 1.420 mm

Cylinder height: 1.200 mm

Total height of tank: 3.300 mm

SKU: 425861



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1700

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.200 mm

Internal diameter: 1.330 mm

Total Height: 3.300 mm

Outer diameter: 1,420 mm



Stirrer

Power (kW): 1,50

Speed (RPM): 72

Mer

Heat Exchanger: RVS 304

Isolated: No