

17200 liter tank in Acid-proof 316



271 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, Aisi 316; Pitting corrosion on the inside of the tank; Metallic discolouration inside

Volumetric volume (L): 17.200 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 43 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN150

Agitator: yes

Power: 11

Top: 14,10 mm

Cylinder: 10 mm

Bottom: 10,10 mm

Internal diameter tank: 2.400 mm

Cylinder height: 3.250 mm

Total height of tank: 6.250 mm

SKU: 410390



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 200 °C

Mobile Tank: No, it is not.

Övrig information: Chemistry; 4 support brackets, Aisi 316; Pitting corrosion on the inside of the tank; Metallic discolouration inside; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 6 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 17200

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 3.250 mm
Internal diameter: 2,400 mm
Total Height: 6.250 mm

Stirrer

Power (kW): 11

Tjocklek på tank

Bottom: 10,10 mm
Cylinder: 10 mm
Top: 14.10 mm

Mer

Isolated: No