

17620 liter tank in Stainless 304



226 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 510 mm; height-adjustable dome screws of the feet are no longer present; 1 small pressure point in the insulating jacket; pipe end cut flush

Volumetric volume (L): 17.620 L

Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar



Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 65

Agitator: yes

Number of revolutions: 16 / 33

Power: 1.2 / 2.2

Cylinder: 4 mm

Bottom: 3,90 mm

Internal diameter tank: 2.500 mm

Outer diameter tank: 2.600 mm

Cylinder height: 3.000 mm

Total height of tank: 5.700 mm

SKU: 486287



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: insulated

Max. Service Temperature: 95 °C

Mobile Tank: No, it is not.

Övrig information: Dairy; Manhole diameter approx. 510 mm; height-adjustable screws of the feet are no longer present; 1 small pressure point in the insulation jacket; pipe end cut flush; we can't give any guarantees

Additional Information2: about the agitator

Agitator: Yes

Overpressure: 0,50 bar

Complete Drainage: Yes

Vacuum Pressure: 0,50 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 17620

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 3,000 mm
Internal diameter: 2.490 mm
Total Height: 5.700 mm
Outer diameter: 2.600 mm

Stirrer

Power (kW): 1.2 / 2.2
Speed (RPM): 16 / 33

Tjocklek på tank

Bottom: 3.90 mm
Cylinder: 4 mm

Mer

Isolated: Yes