1850 liter tank in Acid-proof 316

224 000 SEK /st exkl moms

Additional information: pharmacy; outlet fitting is missing
Volumetric volume (L): 1.850 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 100 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 100 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: available
Agitator: yes
Number of revolutions: 300
Power: 1,50
Cylinder: 5 mm

Bottom: 6,50 mm
Internal diameter tank: 1.200 mm
Outer diameter tank: 1.350 mm
Cylinder height: 1.250 mm
Total height of tank: 3.400 mm

SKU: 394451

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 100 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; outlet fitting is missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 4 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 1850

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 1.250 mm
Internal diameter: 1.200 mm
Total Height: 3,400 mm
Outer diameter: 1.350 mm

Stirrer

Power (kW): 1,50
Speed (RPM): 300

Tjocklek på tank

Bottom: 6,50 mm
Cylinder: 5 mm

Mer

Heat Exchanger: RVS 304
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se