

1850 liter tank in stainless steel 304



234 000 SEK /st exkl moms

Additional information: bump at the insulation jacket

Volumetric volume (L): 1.850 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 6 Bar

Max. working temperature: 100 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: clamp

Agitator: yes

Number of revolutions: 300

Power: 1,50

Internal diameter tank: 1.178 mm

Cylinder height: 1.500 mm

Total height of tank: 3.350 mm

Empty weight tank: 850

SKU: 488058



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 4 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 1850

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 1.500 mm
Internal diameter: 1.178 mm
Total Height: 3.350 mm

Stirrer

Power (kW): 1,50
Speed (RPM): 300

Mer

Isolated: Yes
Weight: 850