

200 liter tank in Acid-proof 316



145 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HILA

Additional information: delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

Volumetric volume (L): 200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: half hinging lid °

Shape of tank: cylindrical

Bottom type: conical 10 °

Total discharge: yes

Fixation points: 3 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Number of sections: 1

Water pressure HE: 3 Bar

Hydraulic test pressure: 4,50 Bar

Contact surface cylinder: 0,75 m²

Connection HE: 1" BSP

Working temperature HE cylinder: 100 °C

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851



Total outlet valve: no, optional

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Insulation body: yes

finish of the outer jacket: welded

Insulation thickness: 40

Distance from outlet to ground: 250 mm

Outer diameter tank: 750 mm

Cylinder height: 550 mm

Total height of tank: 1.700 mm

Empty weight tank: 130

SKU: 376109

Mer information



Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: isolert med varmeveksler

Max. Service Temperature: 100 °C

Maximum Product Density: 1200

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Additional Information2: Ra=<0.8µm

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 10 °

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 200

Equipment

Agitator flange: Yes

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 40 mm

Technical Drawing Available: Yes

Outlet Type: DIN11851



Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 550 mm
Outlet Height to Ground: 250 mm
Total Height: 1.700 mm
Outer diameter: 750 mm

Heat exchangers

Heat exchanger connection: 1" BSP
Operating Temperature Heat Exchanger Cylinder: 100 °C
Bottom hydrostatic test pressure: 4,50 bar
Hydrostatic test pressure: 4,50 bar
Cylinder Contact Surface: 0,75 m²
Position värmeväxlare: the complete cylinder
Type of Heat Exchanger on Cylinder: dimple jacket
Water Pressure Heat Exchanger: 3 bars

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 3 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded
Jacket insulation: Yes
Insulation material: Rockwool

Mer

Heat Exchanger: RVS 304

Insulation Thickness OW: 40

Isolated: Yes

Weight: 130