

200 liter tank in Acid-proof 316



106 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA

Additional information: delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

Volumetric volume (L): 200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic



Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 3 non adjustable feet

Gasket manway(s): EPDM
Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes
CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm

Outlet type: 11.850
Total outlet valve: no, optional
Agitator: no, optional
Agitator type: propeller agitator
Position engine: at the top

Number of revolutions: 1.500
Power: 0,37
Voltage: 400 V - three-phase
Agitator type 2: propeller agitator
Position engine: at the top



Number of revolutions: 680

Power: 0,12

Voltage: 400 V - three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 670 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 676 mm

Cylinder height: 550 mm

Total height of tank: 1.118 mm

Empty weight tank: 70

SKU: 375164

Mer information



Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: single-skin

Max. Service Temperature: 80 °C

Maximum Product Density: 1200

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Additional Information2: Ra=<0.8µm

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 10 °

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 200

Equipment

Agitator flange: Yes

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 40 mm

Technical Drawing Available: Yes

Outlet Type: 11.850

Material Overview

Material: Acid-resistant 316

Fixing point(s): RVS 304



Tank Dimensions

Cylinder Height: 550 mm
Internal diameter: 670 mm
Outlet Height to Ground: 250 mm
Total Height: 1.118 mm
Outer diameter: 676 mm

Stirrer

Power (kW): 0,37
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 1.500
Voltage: 400 V – three-phase

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 3 mm

Mer

Isolated: No
Weight: 70