

200 liter tank in Acid-proof 316



36 000 SEK /st exkl moms

Additional information: Vessel hangs in former stainless steel tilting frame (currently cannot be tilted); vessel open at the top with screwed, hinged stainless steel protective grille; outlet with plunger (would have to be reworked on site; plunger does not close tightly)

Volumetric volume (L): 200 L

Pressure in tank: pressure



Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: open

Total discharge: yes

Volume: 35 L

Max Overpressure: 4 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 1.450

Power: 2,20

Internal diameter tank: 740 mm

Outer diameter tank: 780 mm

Total height of tank: 1.850 mm

SKU: 483860



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: Tank hangs in a former stainless steel tilting frame (currently not tiltable); tank open at the top with a screwed-on, foldable stainless steel protective grille; outlet with plunger (requires

Additional Information2: on-site modification; plunger does not close tightly); we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 200

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Internal diameter: 740 mm

Total Height: 1.850 mm

Outer diameter: 780 mm

Stirrer

Power (kW): 2,20

Speed (RPM): 1.450

Mer

Isolated: No